



# HIGH PRESSURE

## Suitable for Sprinkler System & Fire Fighting

- Compact & lightweight high pressure pump
- 3 ways delivery flange [2"x1, 1"x2] (SERM-50V)



SEM-50V



SEM-50V Image

### Specifications

	Model	SEM-50V	SERM-50V
PUMP	Connection Dia	50 mm (2")	Suction: 50 mm (2") Delivery: 50 mm (2") / 25 mm (1")
	Connection Thread	Outer Pipe Thread BSP	
	Total Head	50 m (164 ft)	90 m (295 ft)
	Delivery Volume	500 L/min (132 USG/min)	
	Max. Suction Head	8 m (26 ft)	
ENGINE	Type	Air-cooled 4-cycle Gasoline Engine	
	Model	Mitsubishi GM 132 Hi-Revolution	Mitsubishi GM 182 Hi-Revolution
	Exhaust Volume	126 cc	181 cc
	Rated Output	2,1 kW (2,8 PS) / 3600 rpm	3,3 kW (4,5 PS) / 3600 rpm
	Max. Output	2,9 kW (4,0 PS) / 4800 rpm	4,4 kW (6,0 PS) / 4800 rpm
	Fuel	Automotive Unleaded Gasoline	
	Fuel Tank Capacity	2,5 L (0,66 USG)	3,5 L (0,92 USG)
	Continuous Operating Time	Approx. 2 hrs	
	Starting Method	Recoil Starter	
	Standard Accessories	1 Strainer 3 Hose Bands 1 Hose Coupling 1 Quick Coupling 1 Engine Tool	1 Strainer 3 Hose Bands (φ 60) 2 Hose Bands (φ 32) 1 Coupling Set (50 mm) 1 Closing Plate (50 mm) 2 Nipples (25 mm) 1 Quick Coupling 1 Engine Tool
Gross Weight	28 kg (61.7 lbs)	38 kg (84 lbs)	
Dimensions LxWxH (mm)	510 × 402 × 440	555 × 450 × 468	
Packing Unit	1		



SERM-50V

### Performance Curve

